



OIL&AIR VALUE

FORK (Damper : Torco Lite RFF 7.5wt, Lower leg/Air Spring : XF Pure Slick Fluid)

Model		Damper Oil(c.c)	Air Spring Oil(c.c)	Lower leg Oil(c.c)
RC32	RC	Closed cartridge	10	Don't put oil
MIG	RC	Closed cartridge		Don't put oil
SLIDE(32)	RL	140		15/per leg
X32	R	125		
VELVET	2 Pieces RL	140		15/per leg
	1 Pieces RL	70		15/per leg
SLANT	RC	Closed cartridge		Don't put oil
SWEEP	HLR	bleed		15/per leg
TRACE34 McQueen SLIDE Boost	RL/R	70		15/per leg
VENGEANCE	HLR/RC	85		20/per leg
	R	fill		
METRIC RV-1	Twin tube HLR/RC	100		
	Roughcut HLR	bleed		
	R	Damper oil:fill IFP Depth:110mm air pressure:50psi		
TRACE36	RC	Closed cartridge	Don't put oil	
	HLR	bleed	20/per leg	
REVEL-X	RC HLR	bleed	30(fill from left crown)	

SHOCK (use Torco Medium RSF 10wt)

Model	Damper Oil(c.c)	Air sleeve Oil(c.c)
Microlite series	fill	5
O2 series		
Stage series		
Vector Air series		

HILO(use Mobil Multipurpose ATF Oil 7.5wt)

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)
27.2	100	65	28
30.9	100	70	18
31.6	100	70	18
30.9	125	78	18
31.6	125	78	18

HILO SL(use Mobil Multipurpose ATF Oil 7.5wt)

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)
30.9	125	90	14
31.6			

HILO SLS(use Torco Lite RFF 7.5wt)

Diameter(OD)	Traval(mm)	Oil(c.c)	Air(psi)	IFP Deepth(mm)
30.9	125	fill	35	15
31.6	150			